

# SCOOT 4

- SYNTHETIC -

REGULAR


Standards : JASO MB – API SL



## Available grade:

10W30 - 10W40

**Scout 4** is a synthetic lubricant for 4-stroke scooters, designed for regular use. Its formula will protect your engine and improve fuel efficiency.



## Packaging:

## Technical data:

TEST	METHOD	TYPICAL VALUES		UNITS OF MESURE
		10W30	10W40	
DENSITY AT 20° C	ISO12185	0,869	0,869	G/cm <sup>3</sup>
VISCOSITY AT 100° C	ASTM D445	11,5	14,5	mm <sup>2</sup> /s
VISCOSITY AT 40° C	ASTM D445	80	99,8	mm <sup>2</sup> /s
VISCOSITY INDEX (VIE)	ASTM D 2270	135	150	-
FLASH POINT	ASTM D92	226	228	°C
POUR POINT	ASTM D97	-33	-30	°C
TBN	ASTM D2896	8,5	8,5	mgKOH/g
TAN	ASTM D664	2,12	2,31	mgKOH/g
JASO N°	-	M033IPN021	M033IPN020	-



La Meunière - CS 10001 - FR 13480 CABRIÈS - TÉL. : +33 4 42 94 05 65 - Fax : +33 4 42 94 05 66

info@ipone.fr - www.ipone.com - /iponelube - /iponelube - iponelube